



9	Gasket(G-006-R)	1	Rubber	Orange
8	Retaining ring(W-020)	1	SK-5	Nickel
7	Spring(W-123-SK5)	1	SK-5	Nickel
6	Washer(W-021-I)	1	Iron	Nickel
5	Shell(S-009)	1	Brass	Nickel
4	Ferrule(F-010)	1	Brass	Nickel
3	Dielectric(D-009)	1	Delrin	White
2	Pin(C-02004)	1	Brass	Gold
1	Body(B-02006)	1	Brass	Nickel
NO	Description	Qty	Material	Finish

UNLESS OTHERWISE SPECIFIED		* MAJOR DIMENSION		APPROVED	
1 REMOVE ALL BURRS		UNLESS OTHERWISE		CHECKED	
2 BREAK ALL CORNERS & EDGES TO 15 MAX		NOTE: TOLERANCES			
3 CHAMFER 15° & 45°		0.5 6 ±0.2		DRAWN 黃存欣	
4 DIAMETERS ON COMMON CENTERS		6.30 ±0.4			
5 TO BE CONCENTRIC WITH CENTER		30 120 ±0.6		DRAWN DATE 08/06/01	
6 ALL DIMENSIONS ARE AFTER PLATING		20 315 ±1.0			
		ANGLES 1°		FILE NO. D:\DWG\COMPOSE\BNC\BNC-1301-F1-DGN	
SCALE	4/1	UNIT	MM		

<h1>HO CHIEN</h1> <p>www.hochien.com</p>		TITLE	
		BNC MALE CRIMP 50(ohm)	
DRAWING NO.		REV B	
BNC-1301-F1-DGN			