



PCB LAYOUT
(Top View)

DR. DATA

1. Electrical Char.

- Insulation Resistance : 500M-0hm Min.
- Contact Resistance : 20milli-0hm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC
- Dielectric Voltage : 1,000 RMS 60 Sec. Min.

2. Physical Char. RoHs Compliant

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black/Medium Gray Color
- Spring Wire : 0.45mm Dia. Phosphor Bronze
- Gold Plating Over Nickel
- Temperature Range : - 25 +90 C
- Durability : 500 Mating cycles Min.

HC-010-26-X-X

B=6p2c, C=6p4c
D=6p6c

Gold plated
1=15u, 2=30u
3=50u, 4= 6 u

HO CHIEN
www.hochien.com

TITLE
RJ11 or RJ12 LOW PORFILE FLANGE PCB JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-010-26-X-X

SCALE SIZE DWG. NO. 9666 SERIES

DO NOT SECALE DRAWING	TOLERANCES UNLESS OTHERWISE NOTED	INCH	MM	DR.	DATA
 THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00±0.01	00±0.25	CK'D	SEP-13 '04
		000±0.005	000±0.13	Johnn	SEP-13 '04
	ANGLE +0°30'	RADIL	+0.45 -0.15	APP'D	SEP-13 '04
				Billy	

DWG. NO.

AS010010