



1	2	40902	2 ROW HEADER PLASTIC .100 X .100
2	52	P15-54-2.732	.025 SQ. PIN .100 PITCH
FIND	QTY	PART NO.	DESCRIPTION

LIST OF MATERIALS

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES  
AND TOLERANCES ARE:

FRACTIONS	DECIMALS	ANGLES
±1/64	.XX ± .02 .XXX ± .010	±1°

DRAWN BY:	DATE:
FA	03.21.05
APPROVED:	DATE:

MATERIAL:	SEE NOTE 1
-----------	------------

FINISH:	SEE NOTE 2
---------	------------

**HO CHIEN**  
*www.hochien.com*

TITLE: HEADER, STACKING, .100 PITCH  
2 ROW BOARD SPACER

CAT. NO:	SIZE	GAGE NO.	DWG NO:	REV
	A		2542-2-2X26G-01	*

SCALE:	4:1	TOOL:	T00363	SHEET	1 OF 1
--------	-----	-------	--------	-------	--------

2. G - GOLD FLASH 3-5 MICROINCHES PER ML-G-45204 TYPE II, OVER NICKEL PLATE 50 MICROINCHES THICK PER QQ-N-290

1. MATERIALS: INSULATOR - BLACK, 30% GLASS FILLED THERMOPLASTIC, 94V-0 RATED OPERATING TEMP RANGE: -65°C TO 250°C.

NOTES: UNLESS OTHERWISE SPECIFIED