


PCB LAYOUT
(Top View)



SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black / Medium Gray Color
- Spring Wire : 0.45mm Dia. Phosphor bronze
Gold Plating Over Nickel
- Temperature Range : - 40°C / +85°C
- Durability : 500 Mating cycles Min.

HC-011-6-X-LX

B=6p2c, C=6p4c
D=6p6c

Gold plated 1=15u, 3=50u
2=30u, 4= 6 u

HO CHIEN

www.hochien.com

TITLE

RJ11 or RJ12 Mini Low Profile PCB Jack
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-011-6-X-LX

SCALE SIZE DWG. NO. 9614 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00±0.01	00±0.25	Steven	MAR-01 '06
		000±0.005	000±0.13	Johnn	MAR-01 '06
	ANGLE +0°30'	0000±0.002	0000±0.05	Billy	MAR-01 '06

DWG. NO. **AS011002-1**