



## SPECIFICATION :

### 1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

### 2. Physical char.

- Housing : Nylon (UL 94V-0)  
Nylon 46 Temperature 260C
- Color : Black Color
- Spring Wire : 0.45mm Dia. Phosphor bronze  
Gold Plating Over Nickel
- Temperature Range : - 40°C / +85°C
- Durability : 500 Mating cycles Min.

**HC-012-6-X-RX-N** ← FLANGELESS

B=6p2c , C=6p4c  
D=6p6c

Gold plated 1=15u , 3=50u  
2=30u , 4= 6 u

**HO CHIEN**

www.hochien.com

TITLE

**RJ11 or RJ12 TOP ENTRY PCB JACK**  
UL & cUL FILE NO. E131820

**MODULAR JACKS ASSY FOR**  
**HC-012-6-X-RX-N**

SCALE SIZE DWG. NO. 9607 SERIES

| NOT SCALED DRAWING            | TOLERANCE UNLESS OTHERWISE NOTICE | INCH       | MM                                 | DR.            | DATE       |
|-------------------------------|-----------------------------------|------------|------------------------------------|----------------|------------|
| <p>THIRD ANGLE PROJECTION</p> | LINEAR                            | MM<br>INCH | 00±0.01<br>000±0.005<br>0000±0.002 | Steven<br>CK'D | OCT-02 '07 |
|                               | ANGLE                             | +0°30'     | RADIL                              | John<br>APP'D  | OCT-02 '07 |
|                               |                                   |            |                                    | Billy          | OCT-02 '07 |

DWG. NO.

**AS012037-1**