

**SPECIFICATION :**


**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

**2. Physical char.**

- Housing (Option) :
  - PBT Glass Filled (UL 94V-0), Soldering Temperature:235°C
  - Nylon (UL 94V-0), Soldering Temperature:260°C
- Color : Black Color
- Spring Wire :
  - 0.45mm Dia. Phosphor bronze Gold Plating Over Nickel.
- Shielded : Brass Plating Nickel
- Temperature Range : - 40°C / +85°C
- Durability : 500 Mating cycles Min.

**HC-019-9-X-XX**



**HO CHIEN**  
www.hochien.com

TITLE

Very low profile Side Entry PCB Jack  
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR. <i>Steven</i>	DATE JUL-01 '08
-----------------------	--------------------------------------	------	----	----------------------	--------------------