



Underwriters Laboratories Inc.

File E189529

Vol. 1

Issued: 4-28-98

2800 N.W. Lake Road
Clemas, WA 98607-8542
United States Country Code (1)
(360) 617-5500
FAX No. (360) 817-8000
http://www.ul.com



FOLLOW-UP SERVICE PROCEDURE
(TYPE L)

COMPONENT - APPLIANCE WIRING MATERIAL
(AVLV2)

Manufacturer: VEGA TECHNOLOGIES INDUSTRIAL
(422799-001) (AUSTRIA) CO
CHYOU FUH LUH INDUSTRIAL ARE
DAH LAANG
DONGGUAN GUANGDONG CHINA

Applicant: SAME AS MANUFACTURER
(422799-001)

Recognized Company: SAME AS MANUFACTURER
(422799-001)

This Procedure authorizes the above Manufacturer to use the marking specified by Underwriters Laboratories Inc. only on products covered by this Procedure, in accordance with the applicable Follow-Up Service Agreement.

The Prescribed Mark or Marking shall be used only at the above manufacturing location on such products which comply with this Procedure and any other applicable requirements.

The Procedure contains information for the use of the above named Manufacturer and the representatives of Underwriters Laboratories Inc. and is not used for any other purpose. It is lent to the Manufacturer with the understanding that it is not to be copied, either wholly or in part, and that it will be returned to Underwriters Laboratories Inc. upon request.

The PROCEDURE, and any subsequent revisions, is the property of UNDERWRITERS LABORATORIES INC., and is not transferable.

UNDERWRITERS LABORATORIES INC.

S. Joe Bhatia
Vice President, Follow-Up Services

Certificate of Compliance

Certificate: 1467038

Master Contract: 221236

Project: 1467038

Date Issued: August 29, 2003

Issued to: Vega Technologies Industrial (Austria) Co.
Qufu Second Industrial Zone
Dalong Town, Dongguan, Guangdong
CHINA

Attention: Mr. Sheng Xiang Liu

The products listed below are eligible to bear the CSA Mark shown



Issued by:

B. Chappell
B. Chappell, P. Eng

Authorized by:

[Signature]
Operations Manager

PRODUCTS

CSA C22.2 No. 210.2-M90 Appliance Wiring Material

Part A: Appliance Wiring Material single conductor construction with PVC insulation, 0.76mm min average thickness, in Sizes 32 - 10 AWG, Class I, Group A, rated at 105C, 600V, FT1, FT2, "0". In all colours except for clear and translucent.

Part B: Appliance Wiring Material single conductor construction with SR-PVC insulation, 0.18mm min average thickness, in Sizes 32 - 10 AWG, Class I, Group A, rated at 80C, 300V, FT1, FT2. In all colours except for clear and translucent.

Part C: Appliance Wiring Material round multiconductor construction with PP insulation, 0.18mm min average thickness, PVC jacket, with min average thickness not less than 0.51mm in Sizes 32 - 10 AWG, Class III, Group A, rated at 60C, 150V, FT2. In all colours except for clear and translucent.

APPLICABLE REQUIREMENTS

CAN/CSA-C22.2 No 210.2-M90

- Appliance Wiring Material Products