


**PCB LAYOUT**



**SPECIFICATION :**

**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

**2. Physical char.**

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze  
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C

**HC-005-6-X-X-N** ← **FLANGELESS**

B=6p2c, C=6p4c  
D=6p6c

Gold plated	1=15u , 3=50u
	2=30u , 4= 6 u

**HO CHIEN**

www.hochien.com

TITLE

**RJ45 SIDE ENTRY PCB JACK  
UL & cUL FILE NO. E131820**

**MODULAR JACKS ASSY FOR  
HC-005-6-X-X-N**

SCALE SIZE DWG. NO.9602 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR. <b>Steven</b>	DATE JUL-30 '04
THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	CK'D <b>Johnn</b>	JUL-30 '04
	ANGLE +0°30'	RADIL	+0.45 -0.15	APP'D <b>Billy</b>	JUL-30 '04

DWG. NO.

**AS005002**