



PCB LAYOUT

SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.
 Contact Resistance : 20milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 120V AC
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : PBT 20% Glass Filled (UL 94V-0)
 Color : Black Color
 Contact Wires : 0.45mm Dia. Phosphor bronze
 Gold Plating Over Nickel
 Temperature Range : - 25 /+90 Deg C
 Durability : 500 Mating cycles Min.

HC-008SH-10-G-X-B1-X1

N - NICKEL PLATED
 T - TINE PLATED

G=10p10c

Gold plated 1=15u, 3=50u
 2=30u, 4= 6 u

HO CHIEN

TITLE

RJ45 SIDE ENTRY SHIELDED PCB JACK
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
 HC-008SH-10-G-X-B1-X1

SCALE SIZE DWG. NO. 9638S SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR	DATE
THIRD ANGLE PROJECTION	LINEAR MM INCH	0.1	0.25	Steven	MAR-31 '03
		0.05	0.13	Johnn	MAR-31 '03
	ANGLE +0°30'	RADIAL	+0.45 -0.15	Billy	MAR-31 '03

DWG. NO.

AS008015