

PCB LAYOUT
(Top View)

SPECIFICATION :


1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.
 Contact Resistance : 20milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 120V AC.
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : PBT Glass Filled (UL 94V-0)
 Color : Black Color
 Spring Wire : 0.45mm Dia. Phosphor bronze
 Gold Plating Over Nickel
 Temperature Range : - 25 /+90 Deg C
 Durability : 500 Mating cycles Min.

HC-040SH 2 F XA2N4



HO CHIEN

www.hochien.com

TITLE
 1x2 8POSITIONS
 SIDE ENTRY SHIELDED PCB GANG JACK
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
 HC-040SH-2-F-X-A2-N4

SCALE SIZE DWG. NO. 9638-S SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR	MM	00±0.01 000±0.005 0000±0.002	Steven	SEP-24 '04
	ANGLE +0°30'	RADIL	+0.45 -0.15	Johnn	SEP-24 '04
MM INCH				APP'D Billy	SEP-24 '04

DWG. NO.

AS040008