



PCB LAYOUT
(Top View)

⚠ Note : Total Cd(adding) Content= 5PPM(ug/kg)
 Test Method : EN122,2001 Method (ICP-AES)
 : Total Pb(Lead) Content= 100PPM(ug/kg)
 Test Method : US EPA3030B (ICP-AES)

SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.
 Contact Resistance : 20milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 120V AC.
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : PBT Glass Filled (UL 94V-0)
 Color : Black Color
 Spring Wire : 0.45mm Dia. Phosphor bronze
 Gold Plating Over Nickel
 Temperature Range : - 25 /+90 Deg C
 Durability : 500 Mating cycles Min.

HC-040SH 4 F X A3 N2

NUMBER OF PORT

F=8P8C

Gold plated 1=15u, 3=50u
 2=30u, 4=6u

HO CHIEN
www.hochien.com

TITLE 1x4 8POSITIONS
 SIDE ENTRY SHIELDED PCB GANG JACK
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-040SH-4-F-X-A3-N2

SCALE SIZE DWG. NO. 9638-S SERIES

DM/G. NO.

AS040013-01

| NOT SCALED DRAWING | TOLERANCE UNLESS OTHERWISE NOTICE | INCH | MM | DR | DATE |
|----------------------------|-----------------------------------|---|----------------------------------|----------------|------------|
| THIRD ANGLE PROJECTION | LINEAR | $\frac{MM}{INCH}$ 00±0.01 000±0.005 0000±0.002 | 00±0.25 000±0.13 0000±0.05 | Steven | JUN-12 '05 |
| | ANGLE | ±0.30° | RADIAL | +0.45 -0.15 | Johnn |
| $\frac{MM}{INCH}$ | | | | Billy | JUN-12 '05 |