



PCB LAYOUT

| | | | | | | |
|-----------------------------|------------------------|-----------------------------------|------------|------------------------------------|-----------------------|--------------------|
| DWG. NO. AS040058 | NOT SCALED DRAWING | TOLERANCE UNLESS OTHERWISE NOTICE | INCH | MM | DR Steven | DATE OCT-27 '03 |
| | THIRD ANGLE PROJECTION | LINEAR | MM INCH | 00±0.01 000±0.005 0000±0.002 | CK'D Johnn | OCT-27 '03 |
| | | ANGLE +0°30' | RADIL | +0.45 -0.15 | APP'D Billy | OCT-27 '03 |

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.45mm Dia. Phosphor bronze
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

HC-040SH-6-F-X-A3-N2



HO CHIEN

www.hochien.com

TITLE
1x6 8POSITIONS
SIDE ENTRY SHIELDED PCB GANG JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-040SH-6-F-X-A3-N2

SCALE SIZE DWG. NO. 9690S SERIES