


PCB Layout



SPECIFICATION :


1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : PBT 20% Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C

HC-062SH-8-F-X-A1-N1



HO CHIEN
www.hochien.com

TITLE
SIDE ENTRY PCB MOUNTING SHIELDED JACK
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
HC-062SH-8-F-X-A1-N1

SCALE SIZE DWG. NO.9662-8S SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
		00±0.1 000±0.05 000 0.02	00±0.25 000±0.13 000 0.5	Steven	MAR-31 '03
THIRD ANGLE PROJECTION	LINEAR	MM INCH		CK'D	
				Johnn	MAR-31 '03
MM INCH	ANGLE +0°30'	RADIL	+0.45 -0.15	APP'D	
				Billy	MAR-31 '03

DWG. NO.
AS062013