



PCB LAYOUT

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance* : 500M-Ohm Min.
- Contact Resistance* : 20milli-Ohm Max.
- Rating Current* : 1.5A Max.
- Rating Voltage* : 120V AC.
- Dielectric Voltage* : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing* : Nylon (UL 94V-0)
- Color* : Black Color
- Spring Wire* : 0.35mm Thickness Phosphor Bronze
Gold Plating Over Nickel
- Temperature Range* : - 25 /+90 Deg C
- Durability* : 500 Mating cycles Min.

HC-111SH-4-F-X-B4-N7

Number Of Port

F=8p8c

Gold plated	1=15u, 3=50u 2=30u, 4= 6 u
-------------	-------------------------------

HO CHIEN
www.hochien.com

TITLE

RJ45 Side Entry Shielded Ganged Jack

UL & cUL FILE NO.131820

**MODULAR JACKS ASSY FOR
HC-111SH-4-F-X-B4-N7**

SCALE SIZE DWG. NO. 9811 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR. Steven	DATE OCT-29 '03
THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$	00 ± 0.01 000 ± 0.005 0000 ± 0.002	00 ± 0.25 000 ± 0.13 0000 ± 0.05	CK'D Johnn	OCT-29 '03
	ANGLE+0'30'	RADIL	+0.45 -0.15	APP'D Billy	OCT-29 '03

DWG. NO.

AS111004