



PCB LAYOUT
(Top View)

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance :** 500M-Ohm Min.
- Contact Resistance :** 20milli-Ohm Max.
- Rating Current :** 1.5A Max.
- Rating Voltage :** 120V AC.
- Delectric Voltage :** 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing :** Nylon (UL 94V-0)
- Color :** Black Color
- Spring Wire :** 0.35mm Thickness Phosphor Bronze
- Gold Plating Over Nickel**
- Temperature Range :** - 25 /+90 Deg C
- Durability :** 500 Mating cycles Min.

HC-1SH-2-F-X-B4-N7-XX

LED 2 Designation : See LED

Number Of Port

F=8p8c

Gold plated 1=15u, 3=50u
2=30u, 4= 6 u

LED 1 Designation :

Code	Forward	Reverse	Code	Forward	Reverse
G	Green	—	2	Yellow	Orange
Y	Yellow	—	3	Green	Red
1	Green	Orange	4	Yellow	Red

HO CHIEN

www.hochien.com

TITLE

RJ45 Side Entry Shielded Ganged Jack With LED

UL & cUL FILE NO.131820

MODULAR JACKS ASSY FOR
HC-111SH-2-F-X-B4-N7-XX

SCALE SIZE DWG. NO. 9811 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
		00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	Steven	AUG-16 '04
THIRD ANGLE PROJECTION	LINEAR $\frac{MM}{INCH}$			CK'D Johnn	AUG-16 '04
$\frac{MM}{INCH}$	ANGLE+0'30'	RADIL	+0.45 -0.15	APP'D Billv	AUG-16 '04