



**PCB LAYOUT**  
(Top View)

**SPECIFICATION :**

**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

**2. Physical char.**

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze  
Gold Plating Over Nickel.
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

**HC-600-22-F-X-D**



**HO CHIEN**

[www.hochien.com](http://www.hochien.com)

TITLE

**DOUBLE DECK GANG PCB JACK**  
**UL & cUL FILE NO. E131820**

**MODULAR JACKS ASSY FOR**  
**HC-600-22-F-X-D**

SCALE SIZE DWG. NO.9600 SERIES

DWG. NO.

**AS600016**

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
THIRD ANGLE PROJECTION	LINEAR	00±0.01 000±0.005 0000±0.002	00±0.25 000±0.13 0000±0.05	Steven	AUG-16 '04
	MM INCH			CK'D Johnn	AUG-16 '04
	ANGLE+0°30'	RADIL	+0.40 -0.15	APP'D Billy	AUG-16 '04