


RECOMMENDED PCB LAYOUT




MATERIAL RoHS Compliant
INSULATOR: GLASS-REINFORCED THERMOPLASTIC (PBT),
 UL94V-0 RATED.
CONTACT: COPPER ALLOY.
PLATING: MATING AREA- SELECT GOLD OVER NICKEL.
 SOLDER AREA- TIN/LEAD OVER NICKEL.

ELECTRICAL
DIELECTRIC WITHSTANDING VOLTAGE: 1,000 VAC RMS.
CURRENT RATING: 3 AMP
INSULATION RESISTANCE: 5,000 MEG. OHMS MIN. AT 500 VDC.
CONTACT RESISTANCE: 20 MILLI OHMS MAX.

MECHANICAL
INSERTION FORCE: 340 GRAMS MAX PER CONTACT PAIR.
WITHDRAWAL FORCE: 28 GRAMS MIN PER CONTACT PAIR.

ENVIRONMENTAL
TEMPERATURE RANGE: -55° TO +85°.

PART NO. 2551-60-01



15,16,17, 18 - contact unload

Cut Pin: A8 • A9 • B8 • B9

				TOLERANCE		HO CHIEN www.chien.com		TITLE: CARDEDGE SLOT 60 P, 2.54mm P							
				LINEAR	ANGLES			PART NO.	2551-60-01						
0		Willson	Nov.15.2005	.XX±0.20	.XX'±	APPD:	Jason	MAT'L.	DWG NO.	2551-60-01					
REV	ECN NO.	NAME	DATE	.XXX±0.10	.XXX'±	CHKD:	Schumi	FINISH:							
						DRWN:	Willson	D'TY:							
												UNITS	SCALE	SHEET	
												MM	1 : 1	1 OF 1	