



## SPECIFICATION :

### 1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

### 2. Physical char.

- Housing : PBT Glass Filled (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.45mm Dia. Phosphor bronze  
Gold Plating Over Nickel
- Temperature Range : - 40°C / +85°C
- Durability : 500 Mating cycles Min.

## HC-012-6-X-LX-N

B=6p2c , C=6p4c  
D=6p6c

Gold plated  
1=15u , 3=50u  
2=30u , 4= 6 u

# HO CHIEN

[www.hochien.com](http://www.hochien.com)

TITLE

**RJ11 or RJ12 TOP ENTRY PCB JACK**  
UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR  
**HC-012-6-X-LX-N**

SCALE SIZE DWG. NO. 9607 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR. <i>Steven</i>	DATE MAR-01 '06
THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	CK'D <i>Johnn</i>	MAR-01 '06
	ANGLE +0°30'	RADIL	+0.45 -0.15	APP'D <i>Billy</i>	MAR-01 '06

DWG. NO.

**AS012004-1**