


PCB LAYOUT
(Top View)



1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.
 Contact Resistance : 20milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 120V AC.
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char. RoHs Compliant

Housing : PBT Glass Filled (UL 94V-0)
 Color : Black Color
 Spring Wire : 0.45mm Dia. Phosphor bronze
 Gold Plating Over Nickel
 Temperature Range : - 25 /+90 Deg C
 Durability : 500 Mating cycles Min.

HC-019-8-F-X

F=8p8c

Gold plated	1=15u, 3=50u 2=30u, 4=6u
-------------	-----------------------------

HO CHIEN

www.hochien.com

TITLE

VERY LOW PROFILE SIDE ENTRY PCB JACK
 UL & cUL FILE NO. E131820

MODULAR JACKS ASSY FOR
 HC-019-8-F-X

SCALE SIZE DWG. NO. 9698 SERIES

NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR.	DATE
 THIRD ANGLE PROJECTION	LINEAR	MM INCH	00±0.01 000±0.005 0000±0.002	Steven	JAN-12 '05
	ANGLE ±0°30'	RADIL	+0.45 -0.15	Johnn	JAN-12 '05
MM INCH				Billy	JAN-12 '05

DWG. NO.

AS019003