



<input checked="" type="checkbox"/> SVT	<input type="checkbox"/> SJT	<input type="checkbox"/> SJTW	AWG
			18
UL/CSA:60°C			
UL/CSA:60°C SHIELDED			
<input checked="" type="checkbox"/>	UL/CSA:60°C~75°C		
UL/CSA:60°C~75°C SHIELDED			
UL/CSA:105°C			
UL/CSA:105°C SHIELDED			
<input checked="" type="checkbox"/> NON MIGRATION		<input type="checkbox"/> MIGRATION	

Power Cord Maximum Rating: 10A @ 125V



RoHS Compliance

UNLESS OTHERWISE SPECIFIED: 1. DIMENSION ARE IN INCHS 2. TOLERANCES: DECIMALES X.XX ±0.25 3. DO NOT SCALE DRAWING 4. REMOVE ALL BURRS AND BREAK SHARP EDGES. PROPRIETARY DOCUMENT THIS DRAWING AND/OR INFORMATION OR SUBJECT MATTER CONTAINED HEREIN, SHALL NOT BE USED, COPIED OR DISSEMINATED IN ANY MANNER, OR FOR ANY PURPOSE, OTHER THAN AS EXPRESSLY STATED BY CDMTOP Enterprises Corp.	CUSTOMER	Ho Chien www.hochien.com			
	R.F.Q. NO.				
	DRAWN	DATE	TITLE Standard AC Power Cord (PC to Wall Power Cord)		
	CHECKED				
CUSTOMER APPROVAL		SIZE	DWG NO.	PART NO.	REV.
				POC-106	A
		SCALE: NONE	RELEASE DATE:	SHEET: 1 OF 1	