



- Voltage Rating : 50 V AC/DC
- Current Rating : 0.5A AC/DC
- Withstanding Voltage : 250V AC/minute
- Insulation Resistance : 50MΩ min
- Temperature Range : - 20°C to + 85°C
- Contact Resistance : 20mΩ max

- FFC/FPC ZIF CONNECTORS (SMT Type)
- Part No. : 1191U
(Right Angle Top Contact Style)
- Poles : 4 - 39
- Material : Contact : Phos. Bronze, Tin Plated
Base : PPS UL94V-0
- Q' ty : 2,000 pcs./Tape & Reel

Poles	Part No.	Dimensions (mm)				
		A	B	C	D	E
4	1191U-4	6.00	7.50	1.50	2.62	1.50
5	1191U-5	6.50	8.00	2.00	3.12	2.00
6	1191U-6	7.00	8.50	2.50	3.62	2.50
7	1191U-7	7.50	9.00	3.00	4.12	3.00
8	1191U-8	8.00	9.50	3.50	4.62	3.50
9	1191U-9	8.50	10.00	4.00	5.12	4.00
10	1191U-10	9.00	10.50	4.50	5.62	4.50
11	1191U-11	9.50	11.00	5.00	6.12	5.00
12	1191U-12	10.00	11.50	5.50	6.62	5.50
13	1191U-13	10.50	12.00	6.00	7.12	6.00
14	1191U-14	11.00	12.50	6.50	7.62	6.50
15	1191U-15	11.50	13.00	7.00	8.12	7.00
16	1191U-16	12.00	13.50	7.50	8.62	7.50
17	1191U-17	12.50	14.00	8.00	9.12	8.00
18	1191U-18	13.00	14.50	8.50	9.62	8.50
19	1191U-19	13.50	15.00	9.00	10.12	9.00
20	1191U-20	14.00	15.50	9.50	10.62	9.50
21	1191U-21	14.50	16.00	10.00	11.12	10.00
22	1191U-22	15.00	16.50	10.50	11.62	10.50
23	1191U-23	15.50	17.00	11.00	12.12	11.00
24	1191U-24	16.00	17.50	11.50	12.62	11.50
25	1191U-25	16.50	18.00	12.00	13.12	12.00
26	1191U-26	17.00	18.50	12.50	13.62	12.50
27	1191U-27	17.50	19.00	13.00	14.12	13.00
28	1191U-28	18.00	19.50	13.50	14.62	13.50
29	1191U-29	18.50	20.00	14.00	15.12	14.00
30	1191U-30	19.00	20.50	14.50	15.62	14.50
31	1191U-31	19.50	21.00	15.00	16.12	15.00
32	1191U-32	20.00	21.50	15.50	16.62	15.50
33	1191U-33	20.50	22.00	16.00	17.12	16.00
34	1191U-34	21.00	22.50	16.50	17.62	16.50
35	1191U-35	21.50	23.00	17.00	18.12	17.00
36	1191U-36	22.00	23.50	17.50	18.62	17.50
37	1191U-37	22.50	24.00	18.00	19.12	18.00
38	1191U-38	23.00	24.50	18.50	19.62	18.50
39	1191U-39	23.50	25.00	19.00	20.12	19.00

0.50mm FFC/FPC ZIF SMT type connectors -Single beam contact style		
ECR	200307-004	2003/07/15
LTR	REVISION RECORD	DATE

HO CHIEN		
www.hochien.com		
APPROVED BY	DATE	SCALE
CHECKED BY	UNIT	
DRAWN BY	VER NO.	SIZE
	B1	A4

TOLERANCE	
.0	±0.30
.00	±0.20
.000	±0.10
PART NO	
1191U-XX	
4 - 39 Pin	