



P.C.B. LAYOUT
BOTTOM VIEW

MATERIAL
 INSULATOR: PBT UL94V-0
 SHELL: Brass, Tin Plated
 CONTACT: Phosphor Bronze, Gold/Tin Plated
 SPRING TOLE: SPS304
 ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C~+105°C
 ELECTRICAL
 CONTACT CURRENT RATING: 1 Amp
 DIELECTRIC WITHSTANDING : AC 500V/min. R.M.S
 INSULATION RESISTANCE: 500MΩmin.at 500V DC
 CONTACT RESISTANCE: 30mΩ Max

DIMENSIONS TOLERANCE	
METRIC	
.0=	±.3
.00=	±.2
.000=	±.XXX
.0000=	±
ANG=	± 2°

單位(UNITS)	mm
數量(QTY)	N/A
材料(MTL)	SEE NOTE
處理(FINISH)	SEE NOTE

HO CHIEN www.hochien.com			
Mini Din 6 position Half Shielding w Spring RoHs			
料號(PART NUMBER)		AMD+1602-041B1	
圖號(DRAW NUMBER)		RAMD1602041B1	
圖檔(FILE NAME .DWG)		E:GCT/A/MD/1/60	
比例(SCALE)	1/1	圖紙(SIZE)	A4
頁次(SHEET)	1	版次(REV.)	A