



◆SPECIFICATIONS

- Current rating: 3A AC, DC
- Voltage rating: 250V AC,DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 800V AC/ minute.
- Contact resistance: 10m Ω Max.

Material: Nylon 66 UL 94V-0

PART No.	Dimension mm	
	A	B
2508-02	2.50	6.60
2508-03	5.00	9.10
2508-04	7.50	11.60
2508-05	10.00	14.10
2508-06	12.50	16.60
2508-07	15.00	19.10
2508-08	17.50	21.60
2508-09	20.00	24.10
2508-10	22.50	26.60
2508-11	25.00	29.10
2508-12	27.50	31.60
2508-13	30.00	34.10
2508-14	32.50	36.60
2508-15	35.00	39.10
2508-16	37.50	41.60

④				GENERAL TOLERANCE	UNIT: mm	DATE	TITLE		
③				. X ± 0.30	X ± 1°		JST SCN 2.5 180 Degree Housing		
②				. XX ± 0.20	. X ±	DRAWN			
①				. XXX ± 0.10	. XX ±	CHECKED			
LTR	NAME	DATE	VERSION	RECORD	APPROVED		VER	SCALE	N/A
1							A	SHEET:	1/1

Ho Chien
www.hochien.com

PROJECTION	PART NO	2508-XX
	DRAWING NO	