



WIRE LIST		
<u>SIDE A</u>		<u>SIDE B</u>
1	Brown	1
2	Red	2
3	Orange	3
4	Yellow	4
5	Green	5
6	Blue	6
7	Purple	7
8	Gray	8
9	Black	9
SHELL	Drain wire	SHELL

1. ELECTRICAL CHARACTER:
- 100 % OPEN&SHORT TESTING
  - WITHSTANDING VOLTAGE:DC 300V 0.1Sec
  - INSULATION RESISTANCE:20M Ohms(Min)
  - CONDUCTIVE RESISTANCE:2 Ohms(Max)

- 2.PACKAGING:
- 1PCS/POLY BAG +LABEL

Description:ASSY,CABLE HORIZONTAL TO VERTICAL  
STANCHION FOR CREEL APPLICATIONS 24"

**CBLA0015-24**

- 3.THE ASSEMBLY REQUIREMENTS TO BE COMPLY  
WITH LATEST IPC/WHMA-A-620 STANDARD

⑥	TUBE	HEAT SHRINK TUBE Ø1.0mm L=15mm COLOR:BLACK	2PCS
④	HOOD	D-Sub9P Conn BLACK ABS PLASTIC Hood, OD:6.0mm with #4-40UNC long screw	2PCS
③	CONNECTOR	D-Sub 9 FEMALE,INSULATION:Black,CONTACT:GOLD Plated , SHELL:NICKEL PLATED,SOLDER TYPE	1PCS
②	CONNECTOR	D-Sub 9 MALE,INSULATION:Black,CONTACT:GOLD Plated , SHELL:NICKEL PLATED,SOLDER TYPE	1PCS
①	CABLE	UL2464 #24AWG*9C+AE OD:6.0mm BLACK PVC JACKET	1PCS
NO	PART NAME	SPECIFICATION	Q'TY

A0	New Drawing For approved	01/26/2015	Tony	
REV.	DESCRIPTION	DATE	APPVL. BY	ECO(N) NO.
UNIT	MM	XX. X.X X.XX	DRAW. BY Andy	01/26/2015
SCALE	NONE	TOLERANCE	CHECKED Tony	01/26/2015
SHEET	1/1	ANGLE ±0.5°	APPVL. BY SL	01/26/2015

**Ho Chien**  
www.hochien.com

DWG  
NAME

ASSY,CABLE HORIZONTAL TO VERTICAL  
STANCHION FOR CREFL APPLICATIONS 24"

DWG NO.

P/N NO.

CA-B4110-0002