



SIDE A
DB9F

SIDE B

WIRE LIST		
SIDE A	Label	SIDE B
3	Black	ACCT -
4	Red	ACCT +
Shell	Green	GROUND

1. ELECTRICAL CHARACTER:
 - a. 100 % OPEN&SHORT TESTING
 - b. WITHSTANDING VOLTAGE:DC 300V 0.1Sec
 - c. INSULATION RESISTANCE:20M Ohms(Min)
 - d. CONDUCTIVE RESISTANCE:2 Ohms(Max)

2.PACKAGING:
1PCS/POLY BAG +LABEL

Description:ASSY,CABLE HORIZONTAL TO VERTICAL STANCHION FOR NO SM CREELS APPLICATIONS 24"
CBLA0019-24

3.THE ASSEMBLY REQUIREMENTS TO BE COMPLY WITH LATEST IPC/WHMA-A-620 STANDARD

⑤	TUBE LABEL	WHITE HEAT SHRINK TUBE Ø2.0mm L=12mm LABEL FOR"GROUND,ACCT +,ACCT -"	3PCS
④	TERMINAL	6.3*0.8mm Fully Insulated Male Disconnects Terminal-Nylon Insulated Crimp Wire Range 22-18AWG AMP2-520103-2 LOCAL	3PCS
③	HOOD	D-Sub9P Conn BLACK ABS PLASTIC Hood, OD:6.0mm with #4-40UNC long screw	1PCS
②	CONNECTOR	D-Sub 9 FEMALE,INSULATION:Black,CONTACT:GOLD Plated , SHELL:NICKEL PLATED,SOLDER TYPE	1PCS
①	CABLE	UL2464 #22AWG*3C过粉 OD:5.5mm BLACK PVC JACKET	1PCS
NO PART NAME		SPECIFICATION	Q'TY

A0	New Drawing For approved	01/26/2015	Tony	
REV.	DESCRIPTION	DATE	APPVL. BY	ECO(N) NO.
UNIT	MM		DRAW. BY	Andy
SCALE	NONE		CHECKED	Tony
SHEET	1/1		APPVL. BY	SL
				01/26/2015
				01/26/2015
				01/26/2015

Ho Chien
www.hochien.com

DWG NAME	ASSY,CABLE HORIZONTAL TO VERTICAL STANCHION FOR NO SM CREELS APPLICATIONS 24"	DWG NO.	
		P/N NO.	CA-B4110-0006