



### PCB LAYOUT

#### TECHNICAL PARAMETERS

TEMPERATURE RANGE: -25~70°

RELATIVE HUMIDITY: 95% (40°)

RATED LOAD: DC30V, 0.3A

MAXIMUM CONTACT RESISTANCE: 0.03Ω

MINIMUM INSULATION RESISTANCE: 100MΩ

TEST VOLTAGE: AC250V, 50Hz

MINIMUM ACTUATING FORCE: 5N

MAXIMUM ACTUATING FORCE: 30N

1	GROUNDING PIN	1	H62 BRASS STRIP, Y = 0.28MM	D. Cu/Sn
2	LONG PIN, LEFT	1	H62 BRASS STRIP, Y = 0.6MM	D. Cu/Sn
3	LONG PIN, RIGHT	1	H62 BRASS STRIP, Y = 0.6MM	D. Cu/Sn
4	CURVED PIN	1	H62 BRASS STRIP, Y = 0.6MM	D. Cu/Sn
5	SHORT PIN, LEFT	1	H62 BRASS STRIP, Y = 0.6MM	D. Cu/Sn
6	SHORT PIN, RIGHT	1	H62 BRASS STRIP, Y = 0.6MM	D. Cu/Sn
7	SHELL	1	ABS	D. Cu/Sn
8	PEDESTAL	1	ABS	D. Cu/Sn
NO.	DESCRIPTION	QTY		

**Ho Chien**  
www.hochien.com

PART NO.

**DS-026**

DIN SOCKET R/A 6 POSITIONS, 240 DEGREES